

SB7560S 75A SCR



FEATURES

- High thermal cycling performance
- High voltage capacity
- Very high current surge capability

APPLICATIONS

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Parameters Summary

 V_{DRM}=1200V, I_{TO}=75A, T_J=125°C


ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T _{STG}	-40 ~ 150	°C
Operating junction temperature range		-40 ~ 125	°C
Repetitive peak off-state voltage (T = 25°C)	V _{DRM}	1200/1600	V
Repetitive peak reverse voltage (T = 25°C)	V _{RRM}	1200/1600/1800	V
Non repetitive surge peak Off-state voltage	V _{DSSM}	V _{DRM} +100	V
Non repetitive peak reverse voltage	V _{PRRM}	V _{RRM} +100	V
RMS on-state current (T = 100°C)	I _{T(RMS)}	75	A
Non repetitive surge peak on-state current	I _{TSM}	700	A
I ² t value for fusing (tp=10ms)	I ² t	2450	A ² ·s
Critical rate of rise of on-state current (I = 2×IGT, tr ≤ 100 ns)	di/dt	150	A/μs
Peak gate current	I _{GM}	5	A
Average gate power dissipation	P _{G(AV)}	2	W

Thermal Resistances

Symbol	Parameter	Value	Unit
R _{th(j-c)}	Junction to case (DC)	TO-3P	0.60
		TO-247	0.55
			°C/W


ELECTRICAL CHARACTERISTICS ($T = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Test Condition	Value
I_{G}	$V_{G} = 12\text{V}$ $R = 1\text{k}\Omega$	20 mA
V_{GD}	$VD=VDRM$ $T_i = 125^\circ\text{C}$ $R = 1\text{k}\Omega$	12 V
I_L	$I_G = 1.2I_{GT}$	100 mA
I_{RRM}	$IT = 50\text{mA}$	200 mA
dV/dt	$V_D = 12\text{V}$ $T_i = 25^\circ\text{C}$	50V/μs


STATIC CHARACTERISTICS

Symbol	Parameter	Value
V_{TM}	$ITM = 140\text{A}$ $tP = 380\mu\text{s}$	$T_i = 25^\circ\text{C}$
I_{DRM}	$V_D = V_{DRM}$ $V_R = V_{RRM}$	$T_i = 25^\circ\text{C}$
I_{RRM}	$V_D = V_{DRM}$ $V_R = V_{RRM}$	$T_i = 125^\circ\text{C}$

Ordering Information Scheme




TO-247 Package Mechanical Data



Ref.	Dimensions		
	Millimeters	Inches	Millimeters
A	4.9	0.193	1.0
B	1.6	0.063	1/2
C	14.35	0.565	5.6
D	0.5	0.020	0.020
F	14.4	0.567	5.6
G	19.7	0.775	0.775
H	15.4	0.606	0.606
J	5.3	0.209	0.209
K	1.2	0.051	0.050
L	2.8	0.110	0.110
P	3.7	0.146	0.146
S	5.35	0.211	0.211

TO-3P Package Mechanical Data



Ref.	Dimensions					
	Millimeters			Inches		
	Min	Type	Max	Min	Type	Max
A	4.40		4.60	0.173		0.181
B	1.40		1.60	0.055		0.062
C	15.48		15.88	0.608		0.635
D	0.50		0.70	0.019		0.027
E	2.70		2.90	0.106		0.114
F	15.92		16.32	0.626		0.642
G	20.27		20.67	0.807		0.831
H	15.15		15.35	0.590		0.604
J		5.45			0.214	0.216
K	1.10		1.30	0.043		0.051
L	1.15		1.35	0.045		0.053
P	2.68		3.08	0.105		0.121
R		4.20			0.165	

FIG.1 Maximum power dissipation versus on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of $I_2 t$ ($dI/dt < 50\text{A}/\mu\text{s}$)




FIG.2: on-state current versus case temperature




FIG.4: On-state characteristics (maximum values)




FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature

